

## **SAINT MARTIN CLAIR - Technical information sheet**

### **Description**

Light Beige Grey colour  
uniform colour with medium grains and speckled with very small shells.

### **Finishes**

Honed, polished, flamed, antique, selection of tooled finishes,  
brushed, aged, sandblasted, chiselled and diamond finishes.

### **Applications**

Interior & exterior commercial and residential flooring and wall cladding.

### **Availability**

Large projects 2000-5000m2  
Available in tiles, cut to-size, architectural elements as well as finished products.

<b>P h y s i c a l</b>	Density	2.62 T/m3	EN 1936	2.63	ASTM C97
	Porosity	1.1%	EN 1936	0.11%	ASTM C97
	Compression	124.0 Mpa	EN 1926	76.8 Mpa	ASTM C170
	Flexion	10.9 Mpa	EN 12372	9.9 Mpa	ASTM C880
	Abrasion	26.80	EN 14157	14.95	ASTM C241
	Freeze	240 cycles	EN 12371		
	Slip	Honed dry 50, wet 19 Flamed dry 73, wet 91	EN 14231		
	Dowel	2500	EN 13364		

The above test were carried out in accordance with European and ASTM Standards by accredited laboratory.  
The above is for general information but should be verified with local standards.

### **Summary**

Uniform beige grey colour, extremely dense and hard wearing, suitable for all interior & exterior applications on large as well as small projects.