

# PIASENTINA VINTAGE

SP



RECOMMENDED APPLICATIONS			
FLOORS & WALLS	SHOWER FLOORS & WALLS	STEAM SHOWERS	EXTERIOR PAVING FREEZE THAW STABLE
YES	YES **	YES **	See Below *

TECHNICAL SPECIFICATIONS			
COMPRESSIVE STRENGTH	TENSILE STRENGTH	WATER ABSORPTION	BULK DENSITY
113 N/mm <sup>2</sup>	10.6 N/mm <sup>2</sup>	9.6%	2450 kg/m <sup>3</sup>

**STOCKED SIZES**

12" x Random Lengths x 3/8" Flamed

\*ALSO AVAILABLE IN FABRIC, HONED & SCORED FINISH

MATERIAL
LIMESTONE
COUNTRY OF ORIGIN
ITALY

- NOTES**
- LENGTHS RANGE FROM 8" TO 32" // SOLD BY THE PATTERN IN MULTIPLES OF 3.35F
  - OTHER SIZES OR FINISHES AVAILABLE VIA SPECIAL ORDER
  - STONE IS A NATURAL PRODUCT. IT IS IMPERATIVE THAT YOU REQUEST JOB SAMPLES AND RANGE PICTURES FOR EVERY JOB
  - \* FLAMED 3/4" THICK MATERIAL IS APPROPRIATE FOR EXTERIOR USE
  - \*\* WET AREA INSTALLATIONS MUST BE PROPERLY SEALED TO AVOID STAINING AND PREMATURE AGING

**RANGE**